FEED-X	В	owl Feeder Specification Sheet	
Company:		Requisitor:	
Phone:	Ext	E-Mail:	

Note: It is necessary to share 3D file and 2D drawing of the product to be fed.

Orientation		Performanc	е
		Outputs	ED-X
		Ouputs quantity:	rails
Clockwise (CW)	Counterclockwise (CCW)	Parts per minute: Bowl capacity:	ppm pcs.
			pco.
	Capacity	amplifiers	
Hopper Fe	eder	Elevator Feed	der
		FEED-X S	3
Volume: or units	m3	Volume: or units	m3

-	Type of Feede	r	
FEED-X Only Bowl	Bowl with Track	With Base Plate	
FEED-X		TED X	
With Noise Cabin	With Structure	With Structure and Cabin	
	Dimensions		
	Dimensions	 Total total based 	
2↔		1 Total track length:	mm
		2 Output track length:	mm
		3 Base length:	mm
3 ←	\rightarrow	4 Width length:	mm
	5	5 Floor to track height: mm	

S	Sensors			
Bowl Feeder Sensor	Track Feeder Sensor			
Electric Specifications				
• Output Type:	• Electric Supply			
NPN PNP	Three-Phase Single-Phase			
• Voltage				
110 v 220 v 440 v				